

## LABEL SPECIFICATIONS

## 410 ECON TD Label 1KR







## Characteristics

Product Description 410 ECON TD, DE 8.2 1KR

Part No: 10111899 Circuit Colour Pink

Label Dimensions (WxH): 40mm x 40mm (1.57" x 1.57")

Distance between labels (D):

Linear Width (L):

External Roll Diameter (ER):

Inner Core Diameter (IC):

2.29mm (0.09")

42 (1.65")

160mm (6.5")

76mm (3")

Face Sheet: White Direct Thermal Paper Adhesive: Permanent, general purpose

Labels per roll: 1,000 Labels per case: 20,000

Weight roll: 0.63kg (1.54 lbs)
Weight case: 12kg (26.4 lbs)

Frequency (MHz) ± 5%: 8.2 Mhz

Electrostatic Discharge Tolerance (ESD): 1.2 kv (minimum)

\*Minimal Order Quantity (MOQ) 20,000 (1 Case)

**Storage conditions:** Keep dry but do not expose to direct sunlight • Recommended storage temperature: 18 to 29 °C Maximum temperature should not exceed 43 °C • Maximum shelf life of RF labels when stored in recommended conditions is 2 years\*\* • Cases should never be stacked more than 5 high

For any questions regarding this or any other labelling process contact your local Checkpoint representative.







<sup>\*</sup>Unless otherwise specified in contractual conditions

<sup>\*\*</sup>RF circuits have no expiry date, however the adhesive has a useful working life of 2 years from the date of manufacture