

ERGOBJÖRN SHELF TROLLEY 200



TERMS & FUNCTIONS

Stabile trolley for order picking in warehouses. The support wheel system with two wheels mounted under the trolley makes it easy to manoeuvre in narrow spaces also with heavy

loads. Shelf edges keep the load in place. Shelf profile of 22 mm round, shiny zinc-coated tubing. The shelves are removable and adapted to standard 600x400 mm trays.

HelgeNyberg

the producer of Ergobjörn



Art. no.	Shelves	Shelf dim.	Length	Width	Height
24121224	2	850x520	1130	520	1110
24121324	2	850x620	1130	620	1110
24121624	2	1250x620	1530	620	1110
24121234	3	850x520	1130	520	1110
24121334	3	850x620	1130	620	1110
24121634	3	1250x620	1530	620	1110

End grid mesh size 100x50 mm

Art. no.	Height
12200140	600
12200144	800

SHELF TROLLEY SERIES 200

A support wheel system (two wheels positioned centrally underneath the trolley) makes the trolley easy to manoeuvre and turn, even with a heavy load. Shelf profile of 22 mm round, shiny zinc-coated tubing. Max. load: 300 kg. Max. load, shelves: 150 kg. Three or four swivel wheels with grey rubber tyres measuring 125x32 mm, ball bearing hubs and safety guard. Two centrally positioned wheels with black elastic rubber tyres measuring 200x50 mm, roller bearing hubs.

HelgeNyberg

HEAD OFFICE / SWEDEN
Industrivägen 2
SE-523 90 Ulricehamn

Phone +46 321 263 00
Fax +46 321 263 01

info@helge-nyberg.com
www.helge-nyberg.com