

XLstep P

Product description

- Handy and robust work platform in a new design.
- Platform size approx. 400 x 300 mm.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Optimum stability thanks to rigid locking bar on both sides.
- Double-sided access.
- Abrasion-resistant, anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



Hints and special features

Complies with EN 14 183



Product features

Coating anodised	Connection Stile-Rung riveted	Load capacity 150 kg	Material Anodised aluminium	Pitch rung/tread 250 mm
Platform length 300 mm	Platform width 400 mm	Standards EN 14183	Stile depth 48 mm	Tread depth 92 mm
Type rung/tread serrated	Warranty 10 years			

Product variants

SKU 40101	SKU 40102	SKU 40103
Base 0,64 m × 0,6 m	Base 0,82 m × 0,68 m	Base 0,99 m × 0,76 m
Number of treads 2 × 2	Number of treads 2 × 3	Number of treads 2 × 4
Overall base width 0.6 m	Overall base width 0.68 m	Overall base width 0.76 m
Platform height 0.49 m	Platform height 0.74 m	Platform height 0.99 m
Transport dimensions approx. 580 mm × approx. 600 mm × approx. 290 mm	Transport dimensions approx. 840 mm × approx. 680 mm × approx. 290 mm	Transport dimensions approx. 1.105 mm × approx. 760 mm × approx. 290 mm
Weight 4.7 kg	Weight 6.1 kg	Weight 7.8 kg
Working height 2.49 m	Working height 2.74 m	Working height 2.99 m